



USB 16 Photo-Isolator-Input

Item-No.: UHO-16 Din-Rail-Module incl.
Item-No.: UPO-16 only board

Produktcode Taiwan:

AUSB16PHOTO/PRO USB 16 PHOTO ISO. INPUT BOARD W/TB PLUGS (whole set)
AUSB16PHOTO USB 16 PHOTO ISO. INPUT BOARD

Label on the card:

USB 16 PHOTO ISOLATOR INPUT BOARD
DCI09041000

Bus: USB 2.0

Description: 16 photo couple input channels

Input maximum load voltage is 30V
By jumper, you can select two range of voltage
0 - 4.5V off and 6V - 20V on. (0 - 20V)
0 - 16.5V off and 18 - 30V on (0 - 30V)
PC817 photo couple chips.
5000V isolation voltage.

16 LED correspond to I/O ports activation status.

Connection:



Easy exchange by interchangeable screw-terminals

Features:

For direct DIN-Rail mounting
Also as board without
DIN-Rail-adapter available

High Speed 8051 μ C Core
USB 2.0 Function Controller
On-Chip Debug
Support USB ID 0~14 SET
POWER DC+5V 0.5mA DC ADAPTOR (optional)

Software/Driver:

Windows-XP Vista use HID-interface and sample for programming,
Linux driver and sample for programming.

Per shipping you receive freshly burned „Decision Computer Germany
service CD“ with current drivers, manuals, installation guidances and
German additional information. The extent depends on the product!

Operating temperature range: from 0 to 33C.
Relative humidity rage: from 0 to 90%.

Package includes the following items:

USB 16P Board
USB cable
Software CD
Englisch manual

Size: 200 mm x 120 mm x 55 mm

Weight (Shipping): 580 Gram
Weight (WEEE): 350 Gram

