



USB 32 Relay

Item-No.: UHR-32 Din-Rail-Module + EMI-Kit incl.
Item-No.: UPR-32 only board

Produktcode Taiwan:

AUSB32RELAY/PRO USB 32 RELAY OUTPUT BOARD W/TB PLUGS (whole set)
 AUSB32RELAY USB 32 RELAY OUTPUT BOARD

Label on the card:

USB 32 RELAY OUTPUT BOARD
 DCI09031800

Bus: USB 2.0

Description: 32 SPDT-Relays - 1 x COM/NO
 Maximum current 500mA
 Maximum 30V

 32 LED correspond to I/O ports activation status.

Connection:



Easy exchange by interchangeable screw-terminals

Features:

For direct DIN-Rail mounting
 Also as board without
 DIN-Rail-adapter available



High Speed 8051 μ C Core
 USB 2.0 Function Controller
 On-Chip Debug
 Support USB ID 0~14 SET
 POWER DC+5V 1A DC ADAPTOR (optional)

EMI-Kit for Din-Rail-Module incl.

USB wiring is very sensitive to EMI errors (mainly sparking when opening contacts). The Kit (U-EMI-1) includes two Würth folded cores for the USB data cable and a Ferrite sleeve for the power supply cable.

Software/Driver:

Windows-XP, Vista, Win7 use HID-interface and sample for programming, Linux driver and sample for programming.

Per shipping you receive freshly burned „Decision Computer Germany service CD“ with current drivers, manuals, installation guidances and German additional information. The extent depends on the product!

Operating temperature range: from 0 to 33C.
Relative humidity range: from 0 to 90%.

Package includes the following items:

USB 32 RELAY Board
 EMI-Kit (DIN-Rail only)
 USB cable
 Software CD
 Englisch manual

Size: 250 mm x 120 mm x 55 mm

Weight (Shipping): 850 Gram
Weight (WEEE): 510 Gram